

# NETTUN@ 7000<sup>open</sup>

## All-in-one POS system with integrated printer

The “Nettun@7000open” is a perfect combination between a traditional cash register and a “PC-based” Point of Sale.

With its 10.1 tiltable touch screen, the integrated thermal printer for receipts equipped with automatic cutter and the adjustable customer display, “Nettun@7000open” is an integrated system for management of Point of Sales in any kind of retail and restaurant business.

The product is characterized by an Intel-based architecture that allows to match operators needs and to manage retail, hospitality, industrial control and other applications.



---

**COMPATIBLE WITH APPLICATIONS DEVELOPED FOR MICROSOFT**

**WIDE I/O CONNECTIONS FOR VARIOUS PERIPHERALS**

---

**FACTORY CUSTOMIZATION OF SPECIFIC MODELS WITH IDENTITY VALIDATION  
OPTIONS ON REQUEST**

---

**POSSIBILITY TO CONNECT DRAWER, EXTERNAL MONITOR, ADDITIONAL KEYBOARD,  
BARCODE READER, SLIP PRINTER**

---



TOUCH SCREEN with tiltable operator panel



EASY paper-roll insertion



FULL CHOICE of interfaces and USB ports

## TECHNICAL SPECIFICATIONS

### MAIN CHARACTERISTICS

<b>Touch Screen</b>	10.1" TFT 16:9 colour monitor Backlit (1024x600) 4-wire resistive touch technology Adjustable tilt
<b>Customer display</b>	LCD Alphanumeric 20x2 Pop-up / adjustable tilt
<b>Mass storage</b>	SSD card ≥ SATA 32 GB capacity

### PRINTER

<b>Technology</b>	Thermal
<b>Speed (line/sec.)</b>	200 mm/sec. - 80 mm
<b>Cutter</b>	Manual & Automatic
<b>Paper loading</b>	Easy loading
<b>Paper roll width (mm)</b>	80 mm
<b>Paper roll diameter (max.)</b>	Up to 80 mm
<b>Fonts characters</b>	2, normal and double height 36/44/52 (25/30/36 with roll width 58/60 mm)

### OTHER CHARACTERISTICS

<b>Sensors</b>	End slip paper Near end slip paper
<b>Connectable devices</b>	Drawer, external monitor, additional keyboard, barcode readers, slip printer, pen drives
<b>Interfaces</b>	2 RS-232 (RJ45 connector) 4 host USB 2.0 1 RJ45 Ethernet 1 RJ45 Drawer connection 1 RJ12 Remote display 1 Customer Display interface 1 VGA Display port 1 HDMI Display port 1 line-out jack 1 microphone jack
<b>Electrical Characteristics</b>	External power supply 24V 60W 100 Vac/60 Hz - 240 Vac/50Hz electric cable Length terminal-Power supply: 1,5m Length Power supply-plug: 1,5 m
<b>Power On/Off button</b>	On the rear side of the machine, inside the connection area
<b>Dimensions (wxdxh)</b>	360x360x180 mm (260 mm with customer display pulled out)

Performance relates to use of the product under optimal conditions.  
Right reserved to modify technical specifications.  
Registered trademarks are the property of their respective owners.  
Nettun@ 7000open is distributed by Olivetti S.p.A.  
(09/2017) - Code: 49586-00-w