

olivetti



IM120D

BANK BACK OFFICE SCANNER

IM120D is a high-performance scanner for bank back offices, **designed to handle large numbers of cheques.**

IM120D supports a wide variety of document formats and cheques, single or double-face scanning for colours or greyscales, **MICR, OCR and barcode reading** through SW libraries, a printer to endorse the back of the document and a double-feed sensor.

IM120D is equipped with **2 output trays** with a capacity of 50 pages each and an 80-page input tray.

It can be equipped with a front and/or rear **self-inking stamp** and prints up to **3 endorsement lines.**

HIGH-PERFORMANCE CHEQUE SCANNER

FRONT/BACK, B/W OR COLOUR IMAGE CAPTURE

2 OUTPUT TRAYS

REAR ENDORSEMENT PRINTER UP TO 3 LINES

FRONT AND/OR REAR SELF-INKING STAMP (OPTIONAL)

SUPPORT FOR HEAVY WORKLOADS



AUTOMATIC DOCUMENT FEEDER



SOLID AND ROBUST MECHANISMS
to handle heavy workloads



TWO OUTPUT TRAYS for automatic ordering

TECHNICAL SPECIFICATIONS

GENERAL CHARACTERISTICS	Basic unit features	<ul style="list-style-type: none"> - Automatic feeder single sheet or continuous - 80 documents input feeder - Front and rear scanner up to 200 dpi resolution, 16/256 levels of grey, colour 24 bit, bitonal image conversion by SW - Two output bins, each up to 50 documents, with full-bin sensor - Double feed and pocket-full sensors - Automatic sorting based on codeline reading 	Power button	ON/OFF switch on the scanner
	Interface	USB 2.0	Software	<ul style="list-style-type: none"> - Drivers for Windows 98/2000/XP/ Vista (32/64)/Seven and Linux - Common API for all IM models - Driver Twain
	Performance	<ul style="list-style-type: none"> - Reading speed: 500 mm/s - Throughput: up to 120 dpm 		
	Document format	<ul style="list-style-type: none"> - Height: 60÷108 mm* (2.2÷4.4") - Length: 150÷216 mm (5.9÷8.5") - Thickness: 0.07÷0.12 mm (3÷5 mils) - Weight: 70÷120 g/m² (0.01÷0.02 lb/sqf) 	Homologation	CE, CSA (C & US), FCC, EN60950 RoHS compliant
	Scanner	<ul style="list-style-type: none"> - Resolution: 100 or 200 dpi - Greyscale: 16 or 256 - Colour: RGB 24 bit - Conversion in B&W 	Options	<ul style="list-style-type: none"> - MICR reader - Recognition OCR, MICR and Barcode by software - Ink-jet printer, up to 3 lines - Front and/or back self-inking stamps
	Image format	DIB, BMP, JPEG, TIFF and TIFF group IV compression		
	Noise	< 53 dB	Dimensions (DxWxH) and weight	410 x 166 x 230 mm (16.1" x 6.5" x 9.1") 7.5 kg (16.1 lbs)
	Power supply	Internal switching adapter 115 or 230 Vca ±10%, 50 or 60 Hz, 80 VA		

(*) Image height up to 108 mm. The unit is able to handle higher documents too

Product performances are referred to an appropriate use under optimal conditions. With the right to change technical specifications. The registered trademarks are the property of their respective owners.

IM120D is distributed by Olivetti S.p.A.

(12/09) - Code 6000712-00

OLIVETTI S.P.A.
VIA JERVIS 77
10015 IVREA (TO) ITALY
www.olivetti.com